

USB4 1.0 ENGINEERING CHANGE NOTICE FORM

Title: Byte Order in Host Memory Descriptors and Data Buffers

Applied to: USB4 Specification Version 1.0

Brief description of the functional changes:

New information about order of bytes in Descriptor Rings in host memory.

Benefits as a result of the changes:

Guidance to Connection Manager and system designer.

An assessment of the impact to the existing revision and systems that currently conform to the USB specification:

None. Complies with existing PCIe-based systems.

An analysis of the hardware implications:

Mapping of descriptors and data buffers shall comply with the ECR.

An analysis of the software implications:

A Connection Manager shall post descriptors and data buffers in host memory in the order defined in the ECR.

A Connection Manager shall read descriptors and data buffers in host memory in the order defined in the ECR.

An analysis of the compliance testing implications:

A Compliance Connection Manager shall verify the byte order within descriptors and data buffers.

USB4 1.0 ENGINEERING CHANGE NOTICE FORM

Actual Change

(a). Section 12.1.1 DW, Byte, and Bit Order

From Text:

A PCIe Host Interface Adapter Layer shall map the payload of a PCIe TLP into a Transmit Descriptor, a Receive Descriptor, or a Transport Layer Packet payload in the following manner:

- For a Transport Layer Packet: Data Byte 0 in the PCIe TLP payload, shall be mapped to bits [31:24] of the first payload DW depicted in Figure 5-1. Data Byte 1 in the PCIe TLP payload, shall be mapped to bits [23:16] of the first payload DW depicted in Figure 5-1, and so on.
- For a Transmit Descriptor: Data Byte 0 in the PCIe TLP payload shall be mapped to bits [7:0] of the first DW of the Transmit Descriptor depicted in Figure 12-4. Data Byte 1 in the PCIe TLP payload shall be mapped to bits [15:8] of the first DW of the Transmit Descriptor depicted in Figure 12-4.
- For a Receive Descriptor: Data Byte 0 in the PCIe TLP payload shall be mapped to bits [7:0] of the first DW of the Receive Descriptor depicted in Figure 12-5 and Figure 12-6. Data Byte 1 in the PCIe TLP payload shall be mapped to bits [15:8] of the first DW of the first DW of the Receive Descriptor depicted in Figure 12-5 and Figure 12-6, and so on.
- Within each byte, bit[i] in the PCIe TLP payload shall be mapped to bit[i] in the corresponding byte of the Transmit Descriptor, Receive Descriptor, or Transport Layer Packet payload.

To Text:

Data Buffers , Transmit Descriptors, and Receive Descriptors shall be stored in host memory in the following manner:

- For a Data Buffer: the lowest-addressed byte of data shall be mapped to bits [31:24] of the first payload DW depicted in Figure 5-1. The following addressed byte shall be mapped to bits [23:16] of the first payload DW depicted in Figure 5-1, and so on.
- For a Transmit Descriptor: the lowest-addressed byte of descriptor data in memory shall be mapped to bits [7:0] of the first DW of the Transmit Descriptor depicted in Figure 12-4. The following addressed byte shall be mapped to bits [15:8] of the first DW of the Transmit Descriptor depicted in Figure 12-4, and so on.
- For a Receive Descriptor: the lowest-addressed byte of descriptor data in memory shall be mapped to bits [7:0] of the first DW of the Receive Descriptor depicted in Figure 12-5 and Figure 12-6. The following addressed byte shall be mapped to bits [15:8] of the first DW of the first DW of the Receive Descriptor depicted in Figure 12-5 and Figure 12-6, and so on.
- Within each byte, bit[i] in host memory shall be mapped to bit[i] in the corresponding byte of the Data Buffer, Transmit Descriptor, or Receive Descriptor.

A PCIe Host Interface Adapter Layer shall map the payload of a PCIe TLP into a **Transport Layer Packet payload** , Transmit Descriptor, **or** a Receive Descriptor, ~~or a Transport Layer Packet payload~~ in the following manner:

- For a Transport Layer Packet: Data Byte 0 in the PCIe TLP payload, shall be mapped to bits [31:24] of the first payload DW depicted in Figure 5-1. Data Byte 1 in the PCIe TLP payload, shall be mapped to bits [23:16] of the first payload DW depicted in Figure 5-1, and so on.

USB4 1.0 ENGINEERING CHANGE NOTICE FORM

- For a Transmit Descriptor: Data Byte 0 in the PCIe TLP payload shall be mapped to bits [7:0] of the first DW of the Transmit Descriptor depicted in Figure 12-4. Data Byte 1 in the PCIe TLP payload shall be mapped to bits [15:8] of the first DW of the Transmit Descriptor depicted in Figure 12-4, **and so on**.
- For a Receive Descriptor: Data Byte 0 in the PCIe TLP payload shall be mapped to bits [7:0] of the first DW of the Receive Descriptor depicted in Figure 12-5 and Figure 12-6. Data Byte 1 in the PCIe TLP payload shall be mapped to bits [15:8] of the first DW of the first DW of the Receive Descriptor depicted in Figure 12-5 and Figure 12-6, and so on.
- Within each byte, bit[i] in the PCIe TLP payload shall be mapped to bit[i] in the corresponding byte of the Transmit Descriptor, Receive Descriptor, or Transport Layer Packet payload.